



Schaeffer Manufacturing Co. DuQuoin
845 N. Hickory
DuQuoin, IL 62832

Sales: (314) 525-2568
Operations: (618) 542-5431



Synthetic 75W-90 GL-5 Limited Slip Gear Oil

Venom® Synthetic 75W-90 GL-5 Limited Slip Gear Oils is a fully synthetic automotive gear oil that provides premium protection under severe conditions, aids in temperature reduction, and axle efficiency.

Venom® Synthetic 75W-90 GL-5 Limited Slip Gear Oil has multi-grade characteristics and is recommended for hypoid gears in moderate and severe service, including shock-loading, and some manual transmissions. Venom® Synthetic 75W-90 GL-5 Limited Slip Gear Oil meets the performance specifications of API GL-5 and is formally approved for Meritor O76-E and O76-N, SAE J2360, and Mack GO-J and GO-H/S specifications. Venom® Synthetic 75W-90 GL-5 Limited Slip Gear Oil is also suitable for use where General Electric D-50E9C and Harnishfeger P&H 474 specifications are required. It is also heavy-duty, severe-service, 500,000-mile drain capable. In addition, Venom® Synthetic 75W-90 GL-5 Limited Slip Gear Oil is formulated with limited-slip additives that meet the performance specifications for service-fill limited-slip applications.

Venom® Synthetic 75W-90 GL-5 Limited Slip Gear Oil also meets API category MT-1 for truck manual transmissions.

Typical Properties:

<i>Product: Venom® Synthetic GL-5 Limited Slip Gear Oils</i>	
Product Code	1451
SAE Viscosity	75W-90
Kinematic Viscosity @ 100 °C cSt (ASTM D-445)	17.0
Kinematic Viscosity @ 40 °C cSt (ASTM D-445)	115.0
Viscosity Index (ASTM D-2270)	160
API Gravity (ASTM D-1298)	30.5