



Schaeffer Manufacturing Co. DuQuoin
845 N. Hickory
DuQuoin, IL 62832

Sales: (314) 525-2568
Operations: (618) 542-5431



Synthetic GL-5 Limited Slip 80W-140 Gear Oil

Venom® Synthetic Limited Slip GL-5 80W-140 Gear Oil is fully synthetic automotive gear oil that provides premium protection under severe conditions.

Venom® Synthetic Limited Slip GL-5 80W-140 Gear Oil has multi-grade characteristics and is formulated to meet the needs of heavy duty axles. Venom® Synthetic Limited Slip GL-5 80W-140 Gear Oil is recommended for hypoid gears in moderate and severe service, including shock-loading, and some manual transmissions. It provides protection from rust and oxidation, and resists deposit formation to protect seals.

Venom® Synthetic Limited Slip GL-5 80W-140 Gear Oil meet Arvin Meritor O-76Q specifications, MIL-L-2105E, Mack GO-J, and, SAE J2360. In addition, limited-slip additives provide coverage for factory-fill limited-slip applications. This gear oil is compatible with synthetic and mineral-based gear lubricants.

Venom® Synthetic Limited Slip GL-5 80W-140 Gear Oil also meets API service categories GL-5 and MT-1 for truck manual transmissions and other heavy duty equipment.

Typical Properties:

Product:	Venom® Synthetic Limited Slip GL-5 80W-140 Gear Oil	
Product Code		90147
SAE Viscosity		80W-140
Kinematic Viscosity @ 100 °C, cSt (ASTM D-445)		30
Brookfield Viscosity @-40C (ASTM D-2983)		80,000 cP