



Schaeffer Manufacturing Co. DuQuoin
845 N. Hickory
DuQuoin, IL 62832

Sales: (314) 525-2568
Operations: (618) 542-5431



Full Synthetic Belt Type CVT Fluid

FORMULA 500® Full Synthetic Belt Type Continuously Variable Transmission (CVT) Fluid is a premium full synthetic transmission fluid specifically designed to be suitable for use in virtually all belt-type continuously variable transmissions. With this approach, this fluid has the ability to provide quality lubrication while simplifying inventories and reducing the chance of using an incorrect fluid. This oil protects against wear while also providing excellent anti-shudder performance.

FORMULA 500® Full Synthetic Belt Type CVT Fluid is suitable for use in the following types of CVTs:

- AC Delco CVT Fluid (P/N 19260800)
- Mopar® CVTF+4 (P/N 05191184AA)
- Subaru Lineartronic CVTF (P/N K0425Y0710)
- Honda Genuine CVT Fluid
- Nissan NS-2, NS-3
- Mitsubishi CVTF-Diaqueen J1/J-4
- Honda CVT Fluid HCF-2
- Esso CVT EZL 799 Fluid (P/N 83220136376)
- GM DEX-CVT® Fluid (P/N 22688912)
- Suzuki CVT Fluid Green 1
- Dodge/Jeep NS-2/CVTF+4
- Toyota Gen. CVT Fluid TC and FE
- Shell Green-1V
- Subaru High Torque CVT Fluid (P/N K0421Y0700)

FORMULA 500® Full Synthetic Belt Type CVT Fluid is not recommended for eCVT or chain-driven CVT transmissions, or in any non-CVT transmission.



Hicks Oils
845 N. Hickory
DuQuoin, IL 62832

Sales: (314) 525-2568
Operations: (618) 542-5431

Typical Properties:

Product: FORMULA 500 [®] Full Synthetic Belt Type CVT Fluid	
Product Code	1074806
Color	Green
Kinematic Viscosity @ 40 °C, cSt (ASTM D-445)	33.9
Kinematic Viscosity @ 100 °C, cSt (ASTM D-445)	7.3
Viscosity Index (ASTM D-2270)	189
Brookfield Viscosity @ -40°C, cP	10,300
Pour Point, °C (°F)	<-45 (<-49)